







Ball table to be used in an assembly area.



Ball units used for air cargo handling.







Ball units used for the handling of large sheets of aluminium.



Ball frame for glass handling.



Air cargo facility.





Bespoke Tool-Rack with sunk Ball Transfer Units



Ball table in industry



Typical material handling system.



Federal Express facility at Hong Kong International Airport.





Alwayse Engineering Limited Miller Street Birmingham B6 4NF England.

Telephone: 0121 380 4700 +44 (0) 121 380 4700

Fax: 0121 380 4701 +44 (0) 121 380 4701

web: www.alwayse.co.uk

FREE Technical Advice:

We offer a free technical advice service - if you are unsure of the correct ball unit to use, ask us. We do not accept liability for the choice of unit if we are not consulted.

email: sales@alwayse.co.uk



Alwayse Engineering Limited

Alwayse Engineering was established in 1939 when a small engineering company, Sheridan Tools, was established. Later its name was changed to "Alwayse" meaning that the units are multi-directional and move in all directions or ways -hence "Alwayse". The distinctive spelling adds to the company's individuality.

The present chairman, Mr L.W. Pinnick, has overseen its growth and development since the late 1940s.

Alwayse Ball Transfer Units are used as part of a conveyor or material handling system to enable loads both light and heavy, to be moved or trans-

ferred in any direction. As the originators of the Ball Transfer Unit over 70 years ago, we have become an important part of the material handling industry.

Whether ball units are used for loading/feeding machines, moving goods/materials, as an alternative to a castor, or in a form of linear operation, they have become an integral part of industry and provide an important and essential service.

Alwayse Ball Units are used in all industries throughout the World and over 2,000,000 are sold every year.

TECHNICAL INFORMATION

DESIGN & CONSTRUCTION



ALWAYSE ball units are a multidirectional, material handling system, manufactured from high quality materials in our Birmingham factory.

They consist of a large load-bearing ball which sits upon many small balls encapsulated in a hemi-spherical cup. The housing can contain a seal to clean the load ball as it rotates. The design greatly reduces friction and allows heavy loads to be moved with a minimum of effort.

Our ball units may be used at any orientation but deviation from the vertical may result in a reduction in the stated load ratings quoted in this catalogue.

FIXING METHODS



There are various methods of fixing Alwayse ball units. A wide range of fittings enable them to be used with various different materials.

Fixing clips are available for most designs - see pages 30 & 31.

MATERIALS

Туре	Load Ball	Support Balls	Housing
13	Carbon	Carbon	Carbon Steel
	Steel	Steel	Bright Zinc
	60-66RC	60-66RC	Plated
14	Nylon 66	Stainless Steel AISI 1420 52-58HRC	Carbon Steel Bright Zinc Plated
15	Stainless Steel	Stainless Steel	Stainless Steel
	AISI 420	AISI 420	AISI 304
	52-58HRC	52-58RC	SelfColour
16	Stainless Steel	Stainless Steel	Carbon Steel
	AISI420	AISI 420	Bright Zinc
	52-58HRC	52-58RC	Plated

ALWAYSE ball units are available in various materials. The material required for your ball units should be quoted when ordering - see page 3 for ordering details.

Lubrication

Each unit is pre-lubricated during manufacture and normally does not require further attention. In certain instances we will advise on lubrication. Greasing or oil points can be incorporated in some units.

Cleaning

For cleaning use a suitable agent such as AC90 or WD40.

Please consult Technical Support for advice.

Most designs have dirt exit holes incorporated in the bearing cup, or these can be added on request.

Shock Loads

When calculating loads, consider the possibility of impact caused by incorrect levels. Spring loaded units will reduce wear and tear if there are regular shock impacts. Shock loading can also be reduced by fitting compressible pads.

Ball units can also be made retractable by other means, such as pneumatic or hydraulic cylinders, cams or levers. They can be programmed to operate in sequence. All stated loads in the catalogue are dynamic loads.

Self Levelling

Can be achieved by fitting rubber pads. This reduces excessive loads on just a few units. Details on request.

Temperature Range

Min. -30°c to max. +70°c continuous, or +100°c intermittent. Special seals may need to be fitted to suit extreme conditions. In clean conditions and without seals +150°c to +200°c are possible, using Type 15 units at reduced loads.

Conveying Speed

Maximum recommended conveying speed is 1 metre per second for steel load balls and 0.25 metres per second for nylon.

Seals

These help resist ingress of dirt and swarf. They can be omitted on request.Woollen felt seals fitted as standard.

Breakaway Coefficient of Friction

The average breakaway friction for new ball units containing steel balls in a good working environment is 0.01 to 0.015 (1% to 1.5% of the load) and 0.02 to 0.025 (2% to 2.5%) for units with felt seals.

BALL TABLES

Red arrows indicate ideal movement.



Vee location

QUANTITY CALCULATION

The weight of the article to be conveyed should be divided by 3. The result will give the maximum load any single ball will bear.

On any accurately levelled or flexible surface, a number greater than 3 may be used. The surface hardness and condition of the article should be considered to avoid ball unit penetration.

Spacing

The pitch is calculated by dividing the narrowest dimension by 3.5, i.e. if the narrowest dimension is 350mm divided by 3.5=100mm pitch

by 3-32-100mm pittin between ball centres. This ensures 3 ball units are always beneath the narrowest dimension of the load at any one time.

->[- 3	5]←
۲	۲	۲	۲	۲
	0	0	0	
۲	0	0	0	۲
۲	0	0	0	\odot
۲	0	0	0	\odot
۲	۲	\bigcirc	۲	۲

TECHNICAL INFORMATION

APPLICATIONS



There are many possible applications for **ALWAYSE** ball transfer units, where loads need to be moved smoothly, precisely and with minimum effort in any direction.

Some typical applications include cargo and baggage handling

QUALITY

ALWAYSE Engineering Limited is quality registered to ISO 9001



We have a policy of continually improving the product range with new innovative and creative ideas using the latest CNC machinery and production/inspection methods.

Our specially designed ball unit test machines, routinely used to test production units, together with many years of research and experience, ensures world-class performance.

ORDERING PROCEDURE

Alwayse provide a completely free technical advice service. We can help you select not only the most suitable ball unit for your application, we can advise on every aspect of layout, design, manufacture and maintenance of your installation.

We strongly recommend you take advantage of this service.

design and manufacture complete assemblies ready for cus-

tomers to use.

1) It is generally only necessary to quote the Product Reference Number (i.e. 1009, 1019 or 530-0) and the Material Type (i.e. Type 13,14,15 or 16).

(shown above), assembly lines, as

a castor, machine loading, sliding-

door systems, machine tables, etc.

Alwayse not only advise and sup-

ply ball units, but also regularly

2) There are however instances where more information is required.

a) Where applicable the length of thread (dimension N) and the spring washer diameter (dimension W), see pages 6-7 & 8-9, also need to be indicated, e.g. 3001-13-25 and 3004-13-16.9.

b) Also, if applicable, quote the special specification code. For example,

> NO (no oil) NS (no seal) NB (nylon ball) PB (phenolic load ball) DE (dirt exit hole) SI (solid steel inner ring).

Black phenolic balls are available in \varnothing 19mm and \varnothing 25.4mm load balls only.

QUICK GUIDE TO THE PRODUCT RANGE

Pages 4,5 Flange Fixing Units

Pages 6,7 Thread Fixing Units



Pages 8,9 Tube Fixing Clamp Fixing Miscellaneous Units

Pages 10,11 Base Fixing Units



Pages 12,13 Mini Ball Transer Units, & "FLOAT-ON"

<u>Pages 14,15</u> Special Ball Units & Fixing Sockets

Pages 16,17 Euro Units



<u>Pages 20,21</u> Hi-Tech, Double Seal, Units

Pages 22,23 Hevi-Load Units 0,1,2 & 3

<u>Pages 24,25</u> Hevi-Load Units 5,6 Die Lifters

Pages 26,27 Spring Loaded Units

<u>Pages 28,29</u> *TUFF* Series Heavy Duty Units

Pages 30,31 Fixing Clips

Page 32 Tee Blocks, Die Tables

















FLANGE FIXING UNITS

0531 - 4001 (inc. 2002 XTRA-TUF)

Features: General purpose. Low profile, dirt exit hole. No seals in 3016 and 3025 units. 2002 XTRA-TUF has heavy duty construction, designed for arduous and dirty conditions. Flushing hole for cleaning, extra large dirt exit hole.



Ball unit Ref. No's 1022 and 1035 with solid steel inner ring (SI) option illustrated with no seal for improved protection from shock loading.



1010 / 1030

Features: Press ball unit into hole to fix, prise out to remove. Units can either be fixed or replaced quickly. Low profile, dirt exit hole.



1502

Features: Low profile, high load capacity. Plastic knife edge seal on load ball. Dirt exit hole. Requires 5mm radius on fixing hole. See 'R'.





3322

Features: Very low profile with large load ball exposure, high load rating, 3 hole fixing, woollen felt seal and single dirt exit hole.



REF No.	FIXING HOLES	BALL SIZE	WEIGHT (KGS)			DI	/EN	SION	IS (r	nm)					MAXI	мим і	DYNAI	MIC LC	DADIN	G (kg)	
		(mm)		A	В		D	E	F	G	Н	ο		ΤΥΡ	E 13	ТҮР	E 14	ТҮР	E 15	ТҮР	E 16
				eter	eight		leter	ge	ckness	entres loles	eter of	e		Carbon Bearing Plated P	Steel s, Zinc Pressings	Nylon Lo Bearing, Plated P	oad Zinc ressings	Stainles Bearings Pressing	s Steel s and s	Stainless Bearings Plated P	s Steel s, Zinc ressings
				Diame	cing He all		/ Diam	er Flan ase	ge Thic	. or Ce xing H	Diame g Hole	ing Ho ieter		E		五	H	E		E	H
				Мах	Work of Ba		Body	Unde to Ba	Flanç	P.C.D of Fi	Hole Fixin	Seati Diam		LOAD UP	LOAD DOWN	LOAD UP	LOAD	LOAD UP	LOAD	LOAD UP	LOAD DOWN
0531	2	12.7	0.022	31	7		19.2 ±0.2	8.2	2.6	24 ±0.2	2.8	20		8	4	4	2	8	4	8	4
3016	2	15.8	0.045	41.3	10.2		22.2 ±0.2	8.3	3.2	30 ±0.2	3.5	23		12	6	8	4	12	6	12	6
3000	2	19	0 087	61	10		29.1	12	3.2	44.5	5 1	30		25	10	20	10	25	10	25	10
3006	3			<u> </u>			±0.2		5.2	±0.2	5										
3025	2	25.4	0.135	56	14.6		34.7 ±0.2	14.6	4	45.5 ±0.2	4.5	35.5									
1000	2	25.4	0.175	73	14.2		37.2 +0 2	15.8	3.5	55.6 +0.2		38.1		55	25	25	10	55	25	55	25
1008	3										5.1										
1022	3	31.7	0.265	73.7	16.2		45.5 ±0.2	19.9	4.2	58.7 ±0.2		46.5									
32742	2													125	55	25	10	125	55	125	55
32743	3	31.7	0.270	73.7	16.2		45.5 ±0.2	19.9	4.2	58.7 ±0.2	5.1	46.5									
2000	2																				
2011	3	39.7	0.515	89	21.4		55.6 ±0.2	24.6	6	70 ±0.2	7	56.5		140	60	N/A	N/A	140	60	140	60
2002	3	39.7	0.635	94.6	21.2		62 ±0.2	27.3	6.3	76.2 ±0.2	7	63.3		225	100	N/A	N/A	225	100	225	100
4001	3	50.8	1.065	120.7	28.3		75.3 ±0.2	30.2	6.3	92 ±0.2	8	76.5		340	100	N/A	N/A	250	100	340	100
 The 1022,	1035, 3274	12 and 327	/43			DI	ИЕМ	SION	IS (r	nm)											
ball units removal o 32742 and	have 7 dir of dirt and I 32743 hav	t exit hole debris. ve no seal	es for	в		D	F	G	н	J	KL	R									
				eight		eter ge	ckness	entres oles	le size oles	ge Size	ght	e									
				king H	i	/ Diam er Flan	ase ge Thio	. or Ce xing H	ted Ho xing H	or Flan	all He	us Unc ge									
				Worl of B		Body Unde	Flan	P.C.D of Fi	Slot of Fi	Majo	Over	Radi Flan									
1502	2	25.4	0.196	12	4	12 0.2 <mark>24</mark>	<mark>.5</mark> 1.7	60.3	5.5 7.7	<mark>69</mark> 5	1 <mark>36.</mark>	5 5		100	50	25	10	100	50	100	50
		_																			
						DIN	/ENS	SION	IS (n	nm)											
				A	В		D	E	F G	i H	0	т									
				neter	Height		meter	, ichnor	Centre	Holes neter	tole										
				x Diar	rking Ball		dy Dia der Fla	Base	D. or	Fixing le Diar	ating F	ole Top ckness									
				Σ Ξ	of		n n	5 5	D.4	운 <mark>동</mark> 및	Sea	Tak Thi									
1010	-	25.4	0.195	73	15.4	3	6.8	15 4.	.8 N/	/A N//	50	5		55	25	25	10	55	25	55	25
1030	-	31.7	0.275	73.7	17	4	4.6	9.5	5 N/	'A <mark>N/A</mark>	50	5		125	55	25	10	125	55	125	55
							.0.2														
						DI	/EN	SION	IS (r	nm)											
				A	в		D	E	F	G	н	0									
				er	ght		ter	σ	ness	ntres les	er of	a									
				lamet	ng Hei		Diame	Flang e	. Thick	or Cer ng Hol	Holes	ig Hole ter									
				Max D	Worki of Bal		Body	Under to Bas	Flange	P.C.D. of Fixi	Hole D Fixing	Seatin Diame									
3322	3	72.2	0.1	45	9.2		33	17 0	36	30	3.5	34		120	60	20	10	80	40	120	60
To order	specify RFF	N° and T	YPE, i.e. 30	16-13	5.0		55	.,.9	5.0		5.5	54		.20		G	eneral Tr	olerance	unless	stated -	10.3mm
	, y n E		_,													50					

Tel: +44 (0) 121 380 4700 Fax: +44 (0) 121 380 4701

www.alwayse.co.uk

sales@alwayse.co.uk

5

ALWAYSE

THREAD FIXING UNITS

3001

Features: Adjustable height, drilled hole fixing.

Optional extras: Additional nuts, alternative thread sizes, dirt exit hole.





Feat

3002

Features: Large support area, greater stability, drilled hole fixing. Optional extras: Alternative thread sizes, dirt exit hole.





1003

Features: Large support area, greater stability, drilled hole fixing. Optional extras: Alternative thread sizes, dirt exit hole.



1009

Features: Adjustable height, drilled hole fixing.

Optional extras: Additional nuts, alternative thread sizes, dirt exit hole.



2001

Features: Adjustable height, drilled hole fixing.

Optional extras: Additional nuts, alternative thread sizes, dirt exit hole.



2005

Features: Large support area, greater stability, drilled hole fixing. Optional extras: Alternative thread sizes, dirt exit hole.



1501

Features: Large support area, greater stability, drilled hole fixing. High load capacity, plastic knife edge seal on main ball. Optional extras: Alternative thread sizes, dirt exit hole.



4004

Features: Adjustable height, drilled hole fixing. High load capacity, dirt exit hole. Optional extras: Grease points can be fitted. Alternative thread sizes. Finish: Body black for types 13 & 16



REF No.	BALL SIZE	MAX TOROUE	WEIGHT (KGS)		DI	MENSIO	ONS (r	nm)				ΜΑΧΙ	MUM	DYNAI		ADIN	G (kg)	
	(mm)	on NUT (Nm)		Α	В		D	N	Р		TYP	E 13	TYP	E 14	TYP	E 15	TYP	E 16
				neter	Height		ameter	f /- 1mm	izes		Bearing: Plated P	s, Zinc ressings	Bearing, Plated P	Zinc ressings	Bearing Pressin	gs and	Bearings Plated P	s Zinc ressings
				lax Diar	lorking f Ball		tody Dia	ength o hread +	hread S									
				2	> 0		-		-	J	UP	DOWN	UP	DOWN	UP	DOWN	UP	DOWN
3001			0.060		24.6		-	25 30 35]								
3002	19	15	0.080	32.1	30.2		25.4	20 25 30	M8		25	10	20	10	25	10	25	10

Ball units are also available with black phenolic load balls (see page 3 suffix PB) of \varnothing 19mm and %25.4mm. Ball transfer units assembled with a black phenolic load ball can be used for glass handling applications.

1003			0.160	20.7	39.7	25.4	18 23 28 33 43		55	25	25	10	55	25	55	25
1009	25.4	15	0.140	35.7	32.5	-	25 30 35 40 50	M8	55	25	25	10	55	25	55	25
1501			0.180	39.5	35.8	-	18 23 28		100	50	25	10	100	50	100	50

*Pattern 4004 can be supplied with other screw sizes or plain shanks.

REF No.	BALL SIZE	MAX TORQUE	WEIGHT (KGS)		D	IMEN	SION	5 (mn	n)			ΜΑΧΙ	MUM	DYNAI	N
	(mm)	on NUT		Α	В		D	Ν	Р*	s	ТҮР	E 13	ТҮР	E 14	
		(inm)		neter	leight		neter	[:] Thread	ses	đ	Carbon S Bearings Plated P	Steel s, Zinc ressings	Nylon Lo Bearing, Plated P	oad Zinc ressings	2
				Max Dian	Working I of Ball		Body Dia	Length of + / - 1mm	Thread siz	Base to to of body	LOAD	LOAD	LOAD		
											UP	DOWN	UP	DOWN	
2001	39.7	20	0.400	55.5	47.62		-	25 30 40 50	M10	_	140	60	N/A	N/A	
2005	55.7	20	0.460	55.5	54.8		49	22 32 42	mile	_	140		170	174	
4004	50.8	25	1.720	89	76		-	UPTO 75	5/8" Whit M16	53.8	340	100	N/A	N/A	
To order,	specify RE	F N°, TYPE	and LENG	TH OF T	HREAD	, i.e. 30	01-13-	25.					G	eneral To	əle



General Tolerance unless stated ±0.3mm

TUBE FIXING • CLAMP FIXING • MISCELLANEOUS UNITS

2004

Excellent as a castor.

w

Α

TUBE FIXING

Features: Tube fixing is achieved by pushing the bush into the tube.

Rotating the unit expands the rubber bush for an interference fit.

Ν

В

W

3004 • 1002 TUBE FIXING

Features: Tube fixing is achieved by pushing the spring washer into a suitable size tube and turning to lock. 3 sizes available - see dimension 'W'. Suitable for use as a castor.





3007 • 1001 • 1021 CLAMP FIXING

Features: The 3007 and 1001 can be fixed to 1mm-10mm thick materials. 1mm-27mm thick materials for the 1021.

The maximum tightening torque is 15Nm for the 3007 and 1001, 20Nm for the 1021.

Optional extras: Dirt exit hole.





1004

Features: Supplied with circlip for loosely fixing to materials up to 6.4mm thick. Dirt exit hole.



1007

Features: Small taper on body allows for interference fixing. Do not strike the ball, use a tube on the flange diameter when fixing. Approx size of taper is 35.8mm top and 35.4mm bottom. Dirt exit hole.



1500

Features: High load capacity. Improved plastic knife edge seal wipes debris off outside the ball. Dirt exit hole.



REF No.	BALL SIZE	WEIGHT (KGS)		DI	MENSIC	DNS (mr	n)		
	(mm)		Α	В		N	Р	w	
			Maximum Diameter	Working Height of Ball		Length of Thread +/-1mm	Thread Size	Spring Washer Diameter	

MAXIMUM DYNAMIC LOADING (kg)



3004	19	0.060	32.1	24.6	40	M6	16.9	25	10	20	10	25	10	25	10
1002	25.4	0.120	39.7	32.5		ino	23.5	55	25	25	10	55	25	55	25
2004	39.7	0.420	55.5	47.6	50	M10	Grip Range 25.4 to 32	140	60	N/A	N/A	140	60	140	60

To order, specify REF N°, TYPE and SPRING WASHER DIAMETER, i.e. 3004-13-16.9.



3007	19	0.160	61	10			3.	2	30	M8		1 to	25	10	20	10	25	10	25	10
1001	25.4	0.260	73	14.2	4	49.7	3	5	0 38.1		25	10	55	25	25	10	55	25	55	25
1021	31.7	0.360	73.7	16.2			4.	2	46.5	6 M10		1 to 27	125	55	25	10	125	55	125	55

		D	MENS	SIONS	(mm))	
A	В		D	E	0	s	т
Maximum Diameter	Working Height of Ball		Body Diameter	Distance Under Flange to Base	Fixing Hole Diameter	Base to Top of Body	Table Top Thickness

1500	25.4	0.160	39.5	35.8	-	-	To suit
1007	25.4				35.8	11.9	To suit
1004	25.4	0.140	45.2	18.4	34.9	12.7	36

55	25	25	10	55	25	55	25
55	25	25	10	55	25	55	25
100	50	25	10	100	50	100	50
			_	_		_	

General Tolerance unless stated ±0.3mm

To order, specify REF N° and TYPE, i.e. 3007-13.

-

-

22.8

3.2

6.4

-

-

BASE FIXING UNITS

3005

Features: Heavy duty fixing. High profile. Drill hole fixing. Optional extras: Dirt exit hole.





1005

Features: Heavy duty fixing. High profile. Drill hole fixing. Optional extras: Dirt exit hole.



1020

Features: Heavy duty fixing. High load capacity. High profile. Drill hole fixing. Optional extras: Dirt exit hole.



2003

Features: Heavy duty fixing. High load capacity. High profile. Drill hole fixing. Optional extras: Dirt exit hole.



4002

Features: Heavy duty fixing. High load capacity. High profile. Dirt exit hole standard. Drill hole fixing. Optional extras: Grease points can be fitted. Finish: Body Black for types 13 and 16.



1006, 1041, 1050

Features: High load capacity. High profile. Dirt exit hole standard. Drill hole fixing. The 1041 and 1050 ball units are similar in design to the 1006 ball unit. 1041 & 1050 are assembled without a seal



1503

Features: High load capacity. High profile. Dirt exit hole standard. Drill hole fixing. Plastic knife edge seal on main ball.



Z
5
m

ТҮРІ	E 13	ТҮР	E 14	ТҮР	E 15	TYPE 16				
Carbon Bearing Plated P	Steel s, Zinc ressings	Nylon Lo Bearing, Plated P	oad Zinc ressings	Stainle Bearing Pressin	ss Steel gs and gs	Stainless Steel Bearings, Zinc Plated Pressings				
B		E		H		즈				
LOAD UP	LOAD DOWN	LOAD UP	LOAD DOWN	LOAD UP	LOAD DOWN	LOAD UP	LOAD DOWN			

REF No.	BALL SIZE	FIXING HOLES	WEIGHT (KGS)			D	IME	NSI	ONS	(mi	m)			
	(mm)			Α	В		F	G	н	Т	J	к	S	
		No. of holes		Max Diameter	Working Height of Ball		Base Thickness	Hole Centres (Length)	Hole Diameter of Fixing Holes	Hole Centres (Width)	Base Plate (Length)	Base Plate (Width)	Base to Top of Body	

1005 25.4 4 0.160 39.7 41.3 2.0 49.2 to 2.4 to 2.4 bit 2.5 4 to 2.4 bit 2.5 4 to 2	3005	19	4	0.100	32.1	32.5	2.0	49.2 ±0.2	6.3	25.4 ±0.2	65	38	-	25	10	20	10	25	10	25	10
	1005	25.4	4	0.160	39.7	41.3	2.0	49.2 ±0.2	6.3	25.4 ±0.2	65	38	-	55	25	25	10	55	25	55	25

1020	31.7	4	0.380	73.7	44.4	2	2.0	47.6 ±0.2	4.8	47.6 ±0.2	58.7	58.7	-	125	55	25	10	125	55	125	55
2003	39.7	4	0.480	55.5	57	2	2.0	47.6 ±0.2	4.8	47.6 ±0.2	58.7	58.7	-	140	60	N/A	N/A	140	60	140	60
4002	50.8	4	2.100	89	76		6.3	89 ±0.2	13.5	89 ±0.2	127	127	54	340	100	N/A	N/A	250	100	340	100

	50.0	35.0	-		20	10	10	5	20	10	20	10
	69.0	51.0	-		55	25	25	10	55	25	55	25
	69.0	51.0	-		30	10	20	10	30	10	30	10
	69.0	51.0	-		100	50	25	10	100	50	100	50
r	nm o	n 58	1 pcc	4			G	eneral T	olerance	unless	stated	+0.3mn

1503	25.4	2	0.200	42	35.8	1.75	60.3 55.9	7.7 5.5	-	69.0	51.0	-

42 31.0

0.042 27.5 20.0

0.160 44.5 30.5

0.145

1041

1006

1050

15.8

25.4

25.4

0.9 40.0 ±0.2 5.2

1.0 60.3 7.7 55.9 5.5

1.0 60.3 7.7 55.9 5.5 -

-

-

Note 1006 & 1050 unit supplied with Slotted fixing holes 7.7 mm x 5.5 mm on 58.1 pcd

MINI BALL TRANSFER UNITS

REF No	Ball Size (mm)	Weight (Kg)	A	В	С	L	Р	Dynamic Load Up Rating (Kg)
11MI-05-13 11MI-05-15	4.8	0.01	13	9	1	24	M6	10
11MI-05-17		0.003	8	6		8.5	M2	5
11MI-06-13 11MI-06-15	6.4	0.02	17	11	2	26	M6	20
11MI-06-17		0.008	13	10.5		16.5	M3	15
11MI-08-13 11MI-08-15	7.9	0.03	18	14	2	32	M8	30
11MI-08-17		0.011	15	12.5		20.5	M4	20
11MI-10-13 11MI-10-15	9.6	0.06	23	20	2	40	M8	40
11MI-13-13 11MI-13-15	12.7	0.1	28	25	3.5	48	M8	50
11MI-16-13 11MI-16-15	15.8	0.05	24	20.5	1	32.5	M6	70
11MI-16-13-FT 11MI-16-15-FT	15.8	0.06	24	20.5	4	52.5	1410	70

Applications

Measuring Equipment

Lightweight Coilholder

Guides for small linear motion (eg photocopier slides)

Transfer of material in clean rooms

Miniature mechanisms

All thread sizes for dimension "P" are metric coarse

Carbon Steel type 13 mini ball transfer units are assembled with a small amount of oil to protect the carbon steel balls from oxidation.

11MI-16-13 & 11MI-16-15 Can be supplied as Flat-Topped "FT" or as angled top

Type 13 & 15







REF No	Balls	Body
11MI-05-17 11MI-06-17 11MI-08-17	Stainless Steel Load Ball Stainless Steel Small Balls	Aluminium Outer Cover Stainless Steel Screw Thread
11MI-05-13 11MI-06-13	Carbon Steel Load Ball Stainless Steel Small Balls	Carbon Steel Outer Cover Stainless Steel Screw Thread
11MI-05-15 11MI-06-15	Stainless Steel Load Ball Stainless Steel Small Balls	Stainless Steel Outer Cover and Stainless Steel Screw Thread
11MI-08-13 11MI-10-13 11MI-13-13 11MI-16-13	Carbon Steel Load Ball Chrome Steel Small Balls	Carbon Steel Outer Cover Stainless Steel Screw Thread
11MI-08-15 11MI-10-15 11MI-13-15 11MI-16-15	Stainless Steel Load Ball Stainless Steel Small Balls	Stainless Steel Outer Cover and Stainless Steel Screw Thread
11MI-16-13-FT	Carbon Steel Load Ball Carbon Steel Small Balls	Carbon Steel Outer Cover Carbon Steel Screw Thread
11MI-16-15-FT	Stainless Steel Load Ball Stainless Steel Small Balls	Stainless Steel Outer Cover and Stainless Steel Screw Thread



mm	Вr	nm	nm	nm	ap Kgs	шш
A ØI	min	max	с С		Load C	ЕØI
35	55	77	38	88	15	13.5
50	73	95	58	106	20	13.5

FIXING: Drill a 14mm dia. hole, Fix socket and adjust height

FLOAT-ON DESIGNED FOR USE IN WET AND DRY CONDITIONS

FLOAT-ON DESIGNED FOR USE IN WET AND DRY CONDITIONS

Ensures smooth movement of materials with delicate or polished surfaces Comes in Red Polyurethane & Black Rubber - 35mm & 50mm Diameter

COMPLETE ASSEMBLY

	BLACK RUBBER	RED POLYURETHANE
35мм вар	ACR 35 R/H OR L/H	ACP 35 R/H OR L/H
35mm s/s	ACR 35 R/H OR L/H S/S	ACP 35 R/H OR L/H S/S
50MM BZP	ACR 50 R/H OR L/H	ACP 50 R/H OR L/H
50mm s/s	ACR 50 R/H OR L/H S/S	ACP 50 R/H OR L/H S/S

STEM, CIRCLIP, WASHER AND BALL ONLY

BZP	s/s
SCW 35 RB R/H OR L/H	SCW 35 RB R/H OR L/H S/S
scw 50 rb r/h or l/h	SCW 50 RB R/H OR L/H S/S
SCW 35 PB R/H OR L/H	SCW 35 PB R/H OR L/H S/S
scw 50 pb r/h or l/h	scw 50 pb r/h or l/h s/s

BALLS ONLY

0.11	BLACK RUBBER	RED POLYURETHANE
35мм	ACR 35b	ACP 35b
50MM	ACR 5OB	аср 50в

 $_{\rm BZP}$ = Bright Zinc Plate, can be used in most applications $_{\rm S}/_{\rm S}$ = Stainless Steel Inox, for the most arduous of conditions

NOTE: When ordering stems/circlip/washers or complete castors please state whether you require R/H (right hand) or L/H (left hand).

FLOAT-ON castors are used for easy handling of other flat sheet materials i.e. Granite, Wood, Plastic, Paper and Card etc.

Shore Hardness; RUBBER 80-85A (30b) POLY 90-95A (48b)





GLIDE-ALWAYSE UNITS & FIXING SOCKETS

This is a simple and inexpensive range of ball transfer units which have a large ball exposure. They are ideal for lighter duties and where there is a cost consideration.

All units are fitted with a seal which simply and effectively removes debris by an internal plastic scraper.

The direction of rotation slightly moves the ball against the seal providing a highly effective cleaning action.

For normal applications steel bearings with zinc plated pressings and components are recommended. However, when used as a castor or in wet conditions stainless steel (Type 15) is recommended.

1700 PLUG FIXING

Features: Plain body, dirt exit hole standard.



1701 BOLT FIXING

Features: Drill hole nut and bolt fixing. Maximum tightening torque is 15Nm.

1702 FLANGE FIXING

Features: Low profile flange fixing, dirt exit hole standard. Seating hole diameter 39mm.





1703 PLATE FIXING

Features: High profile base plate fixing. Drill hole fixing. Dirt exit hole standard.



1709 GRIP NECK FIXING

D

Features: Plastic or steel socket fixing.



1705 GRIP NECK



REF No.	FIXING	BALL SIZE	WEIGHT (kq)					D	IME	NSIC	ONS	(mr	n)					(kg)						
		(mm)		Α	В		D	Е	F	G	н	J	К	L	Ν	Р	S		TYPE 13	TYPE 14	TYPE 15	TYPE 16		
				Maximum Diameter	Working Height of Ball		Body Diameter	Distance Under Flange to Base	Flange Thickness	P.C.D. or Centres of Fixing Holes	Hole Diameter of Fixing Holes	Major Flange Size	Minor Flange Size	Overall Height	Length of Thread or Pin + / - 1mm	Thread Size or Pin Diameter	Base to Top of Body		Carbon Steel Bearings, Zinc Plated Pressings	Nylon Load Bearing, Zinc Plated Pressings	Stainless Steel Bearings & Pressings	Stainless Steel Bearings, Zinc Plated Pressings		
																•								
1700	PLUG		0.10		-			7.8							-	-								
				30.5					-	-	-	-	-		18		24.7							
1701	BOLT				-		26.6	-						33.5	23 28	M8								
1702	FLANGE	25.4	0 12	34.5	12.4			21.1	2	48	5 25	64	44		_	_	23.1		50	20	50	50		
1703	PLATE	0.12	20.5			-		2	2 ±0.2	5.25	04		35.7			26.9								
1709	GRIP NECK		30	50.5	-		26.6	-	-	-	-	-	-	34.7	34.7	7.7	25.9							
To order.	order, specify REF N° and TYPE, i.e. 1700-13.																							

SPECIAL BALL UNITS

ALWAYSE meeting your needs...

we manufacture the widest range of Ball Transfer Units in the world...



...should your application require it, we can design and manufacture a bespoke unit which meets your specific criteria.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT ABOUT YOUR APPLICATION.



EURO UNITS

ALWAYSE Euro Units have a main bearing cup of special toughened steel with a dirt exit hole and a woollen felt seal.

Min. -30°c to max. +70°c continuous, or +100°c intermittent. Special seals may need to be fitted to suit extreme conditions. In clean conditions and without seals +150°c to +200°c are possible, using Type 15 units at reduced loads.

MATERIAL SPEC:

Stainless Steel Pressings	a AISI 304
Stainless Steel Balls	AISI 420
Nylon Balls	NYLON 66

EURO O

Features: Various fixing clips available, dimensionally compatible with the 800 series, see pages 18 & 19.





EURO 2

Features: Easy fitting with a 3 prong builtin clip from top face of ball table, compact and low profile, dimensionally identical to other Euro Unit ball units



EURO 4

Features: Various fixing clips available, coned outer ring. Dimensionally compatible with the 800 series, see pages 18 & 19.



EURO 1



EURO 6

Features: Various fixing clips available. Reinforced coned outer ring and support cup for improved protection against shock loading. Dimensionally compatible with the 800 series. Woollen felt seals are standard except for the 515-6 ball unit.



0
П

TYPE 16 Stainless Steel Bearings, Zinc Plated Pressings

WEIGHT CAPACITY

(kg)

60

60

60

60

160

160

160

160

300

300

300

300

610

610

610

610

REF No.	BALL SIZE	DIMENSIONS (mm)									MAXIMUM DYNAMIC LOADII						
	(mm)	Α	В		D	F	G	н	L		ТҮРІ	E 13	ТҮР	E 14	ТҮР	E 15	ТҮР
		Maximum Diameter	Working Height of Ball		Body Diameter	Flange Thickness	P.C.D. or Centres of Fixing Slots	Hole Diameter of Fixing Slots	Overall Height		Carbon : Bearing: Plated P WEIGHT (KGS)	Steel 5, Zinc ressings CAPACITY (kg)	Nylon Lo Bearing, Plated P WEIGHT (KGS)	oad Zinc ressings CAPACITY (kg)	Stainle Bearing Pressin WEIGHT (KGS)	ss Steel gs and gs CAPACITY (kg)	Stainles Bearing: Plated P WEIGHT (KGS)
515-0			9.5 ±0.2		24 ±0.065	2.8	-	-	21		0.043	60	0.028	10	0.043	38	0.043
515-1	15.8	31					29 ±0.2	3.5			0.043	60	0.028	10	0.043	38	0.043
515-4	15.0	5.					-	-			0.043	60	0.028	10	0.043	38	0.043
515-6							-	-			0.054	60	0.039	10	0.054	38	0.054
522-0	22.2	45			36 ±0.08	2.8	-	-			0.132	160	0.096	20	0.132	100	0.132
522-1			9.8 ±0.2				42 ±0.2	3.5	30		0.132	160	0.096	20	0.132	100	0.132
522-4							-	-			0.132	160	0.096	20	0.132	100	0.132
522-6							-	-			0.165	160	0.130	20	0.165	100	0.165
530-0							-	-			0.278	300	0.182	25	0.278	200	0.278
530-1	30	55	13.8		45	4	51 ±0.2	3.5	37		0.278	300	0.182	25	0.278	200	0.278
530-4			±0.3		±0.08		-	-			0.278	300	0.182	25	0.278	200	0.278
530-6							-	-			0.335	300	0.238	25	0.335	200	0.335
545-0							-	-			0.725	610	0.41	30	0.725	250	0.725
545-1	44.5	75	19		62	4	69 ±0.2	4.3	53.5		0.725	610	0.41	30	0.725	250	0.725
545-4	44.5	75	±0.4	.4	±0.095	4	-	-	53.5		0.725	610	0.42	30	0.725	250	0.725
545-6							-	-			0.887	610	0.57	30	0.887	250	0.887

REF No.	LOAD	DIMENSIONS (mm)													
	SIZE	AB		D	E	F	L	0	т		TYF				
	(mm)	Maximum Diameter (mm)	Working Height of Ball (mm)		Body Diameter (mm)	Distance from under Flange to Base (mm)	Flange Thickness (mm)	Overall Length (mm)	Seating Hole Diameter (mm)	Table Top Material Thickness (mm)		Carbor Bearin Plated WEIGH (KGS)			
15-2	15.8	31	9.5 ±0.2		24 ±0.1	11.5	2.8	21	25.0 25.5	2		0.043			
22-2	22.2	45	9.8 ±0.2		36 ±0.1	20.2	2.8	30	37.0 37.5	3		0.132			
80-2	30	55	13.8 ±0.2		45 ±0.1	23.2	4	37	46.0 46.5	6		0.278			
15-2	44.5	75	19 ±0.2		62 ±0.1	34.5	4	53.5	63.0 63.5	7		0.725			

MAXIMUM DYNAMIC LOADING (kg)

	ТҮРІ	E 13	ТҮР	E 14	ТҮР	E 15	TYPE 16		
	Carbon S Bearings Plated P	Steel 5, Zinc ressings	Nylon Lo Bearing, Plated P	oad Zinc ressings	Stainle Bearing Pressin	ss Steel gs and gs	Stainless Steel Bearings, Zinc Plated Pressings		
	WEIGHT (KGS)	CAPACITY (kg)	WEIGHT (KGS)	CAPACITY (kg)	WEIGHT (KGS)	CAPACITY (kg)	WEIGHT (KGS)	CAPACITY (kg)	
ļ									
	0.043	60	0.028	10	0.043	38	0.043	60	
	0.132	160	0.096	20	0.132	100	0.132	160	
	0.278	300	0.182	25	0.278	200	0.278	300	
	0.725	610	0.41	30	0.725	250	0.725	610	

For load down use as a castor, reduce dynamic load rating by 50%.

To order, specify REF N° and TYPE, i.e 515-0-13.

53 54

CL14 FIXING CLIPS (Please see pages 30 and 31 for CL14 fixing clip dimensions)

REF No.	SUITABLE FOR UNITS
CL14-515	515-0, 515-4, 515-6
CL14-522	522-0, 522-4, 522-6
CL14-530	530-0, 530-4, 530-6
CL14-545	545-0, 545-4, 545-6
To order, specify RE	F N°, i.e CL14-515.

FIXING HOL	E SIZES (mm)
24	+1.0
24	+1.5
36	+1.0
50	+1.5
45	+1.0
	+1.5
62	+1.0
02	+1.5

General Tolerance unless stated ±0.3mm

Tel: +44 (0) 121 380 4700 Fax: +44 (0) 121 380 4701

HEAVY-DUTY UNITS, SERIES 800

HEAVY DUTY 800

Features: High load capacity, low profile, robust construction.



HEAVY DUTY 805

Features: High load capacity, low profile, robust construction. Multi-hole drain plug provides an extra 600% debris hole area to assist in cleaning.



HEAVY DUTY 806

Features: High load capacity, low profile, can be disassembled. Slotted dirt exit hole allows large debris particles to pass through.



HEAVY DUTY 810

Features: High load capacity, low profile, coned outer ring. The 810-12 does not have a flange.



HEAVY DUTY 807, 808

Features: High load capacity, low profile. Slotted dirt exit hole allows large debris particles to pass through. The 808-30 has a polymer scraper seal fitted to resist ingress of dirt.



HEAVY DUTY 820

Features: High load capacity, solid body and robust outer ring for greater durability. Can be dismantled for cleaning. Fixing hole options available on request. Finish Body chemical black for types 13 and 16.



Alwayse Series 800 are solid body steel ball units.

They incorporate a seal and dirt exit hole for maximum efficiency and smooth running.

Our CNC production plant can produce special designs to individual customers requirements.

Easy fixing clips are available, ref no. CL14, for quick and effective fixing, see pages 30 and 31. When used the working height of the ball unit dimension 'B' is increased by 0.3mm.

800 Series Type 15, Stainless Steel

In general ball unit sizes from Ø15.8mm to Ø30mm will have unhardened components typically 303/304 stainless steel.

Ball units with Ø44.5mm, Ø57.1mm, Ø76.2mm and Ø88.9mm balls have hardened bodies. In general balls are hardened 420 Stainless Steel.

805 Heavy Duty Ball Units

Similar to 800 series units, the 805 ball units incorporate a stainless steel multi-hole drain plug for improved cleaning and debris removal, stainless bearings for corrosion resistance, and no seal for easy cleaning and reduced friction.

The 800, 805, 806, 807, 808 and 810 range of ball units are dimensionally compatible with our Euro Unit range of ball transfer units, see pages 16 and 17.

REF No.	BALL SIZE	WEIGHT (KGS)			DI	MENSIO		MAXIMUM	DYNAMIC LO	NAMIC LOADING (kg)			
	(mm)	(1100)	А	В	с	D		F	L		TYPE 13	TYPE 15	TYPE 16
			Vaximum Diameter	Norking Height of Ball	Ball Exposure above Outer Ring	3ody Diameter		lange Thickness	Overall Height		Carbon Steel Bearings, Zinc Plated Pressings	Stainless Steel Bearings and Pressings	Stainless Steel Bearings, Zinc Plated Pressings
800-22	22.2	0.18	45	9.8 ±0.2		36 ±0.08		3.0	30.5		180	120	180
800-30	30	0.38	55	13.8 ±0.2		45 ±0.08		3.4	36.8		350	200	350
800-45	44.5	1.10	75	19		62 ±0.1		3.8	53.5		600	300	600
800-60	57.1	3.80	117	29.5		100 ±0.1		5.0	77.5		1500	1000	1000
805-30	30	0.38	55	13.8 ±0.2		45 ±0.08		3.4	36.8		350	200	350
805-45	44.5	1.10	75	19		62 ±0.1		3.8	53.5		600	300	600
806-30	30	0.35	55	13.8 ±0.2		45 ±0.08		3.4	36.8		350	200	350
807-30	30	0.36	55	13.8 ±0.2		45 ±0.08		3.4	36.8		350	200	350
808-30	30	0.34	55	13.8 ±0.2		45 ±0.08		3.4	36.8		350	200	350
810-12	12.7	0.034	-	-		22 ±0.06		-	17.5		40	26	40
810-15	15.8	0.06	31	9.5 ±0.2		24 ±0.06		3.8	21		70	43	70
810-22	22.2	0.20	45	9.8 ±0.2		36 ±0.08		4.0	30.5		180	120	180
810-30	30	0.37	55	13.8 ±0.2		45 ±0.08		5.0	36.8		350	200	350
810-45	44.5	0.99	75	19		62 ±0.1		4.5	53.5		600	300	600
810-60	57.1	3.93	117	29.5		100 ±0.1		13.1	77.5		1500	1000	1000
820-60	57.1	3.5	-	77.5	16.5	100 ±0.1		-	-		1500	1000	1000
820-76	76.2	8.6	-	103	23	130 ±0.1		-	-		3000	2000	2500
820-90	88.9	11.0	-	115	25	145 ±0.1		-	-		4000	2500	3500
To order, sp	order, specify REF N° and TYPE, i.e. 800-22-13. General Tolerance unless stated ±0.3mm												

General Tolerance unless stated ±0.3mm *Please consult us when mounting in inverted position as a castor, load down.

HI-TECH, DOUBLE SEAL, UNITS

DOUBLE SEAL

This is the first ball transfer design that incorporates double sealing for excluding debris from the bearings.

The top cover seal removes larger particles and the inner knife edge scraper seal skims liquid, paste, fine dust, etc. off the large ball and expels it through side vents.

A dirt exit hole can also be incorporated.

RUST RESISTANT UNITS (Type 15 only)

All parts are of non-rusting material, impervious to the most severe industrial environment and have high impact resistance.

The main bearing track is hardened and has been load and life tested. The ball unit runs equally well inverted or at an angle.

MATERIALS

Steel (Type 13) or stainless (Type 15) load components and bearings.

Hi-Tech Units have the same rated load capacities as the Ø25.4mm Hevi-Load units (see pages 22 & 23). The Hi-tech units have glass re-inforced nylon bodies so their weight is less than half that of the Ø25.4mm Hevi-Load units.

Stainless steel bearings with steel load components (Type 16) are available on request.

CHEMICAL RESISTANCE

High resistance to organic solvents, petrol and oil.

Seek our advice if in doubt.

TEMPERATURE

-30°C upto +100°C.

6025-0

6025-3

F

G

Hevi-load 7123.

Features: High load capacity.

Ball height compatible with

Α

G

J

H DIÁ

Features: High load Capacity. Dimensionally compatible with Hevi-Load 7121.



6025-1

Features: Bolt fixing high load capacity. If used for height adjustment the locknut must remain secured to the body. Maximum tightening torque is 15Nm.



6025-4

Features: High load capacity. Coned flange for smoother onoff transfer.





6025-2

Features: Top flange high load capacity. Dimensionally compatible with Hevi-load 7125.



6025-5

Features: Ideal for shock loading. Stainless steel springs available on request. Compatible with Hevi-load 7136, 7139, 7137, 7135.



В



DIMENSIONS (mm)										
s		(k	g)							
Base to Top of Body		TYPE 13 Carbon Steel Bearings, Zinc Plated Pressings	TYPE 15 Stainless Steel Bearings and Pressings							
38.3		-	240							
		320	-							
38.3		-	240							
		320	-							
38.3		-	240							
		320	-							
38.3		-	240							
		320	-							
38.3		-	240							
		320	-							
	S b b c c c c c c c c c c c c c	S jo d jo sea 38.3 38.3 38.3 38.3 38.3 38.3	S CAPA (k TYPE \$ Earings, \$ F \$ F							

	DI	MENSIC	DNS (m	m)		DYNAMIC SUPPORT
Α	В	С Б		0	w	LOAD (Kg)
Maximum Diameter	Working Height of Ball	Ball Exposure above Outer Rir		M10 Nut Clearance Diameter	Collar Diameter	

6025-5-15A	25 /	Stainless	0 330	50.8	61.9	67	20.0	29		7	100	22
6025-5-13A	23.4	Ferrous	0.550	50.8	01.5	0.7	20.0	50		,	100	5.2
6025-5-15B	25.4	Stainless	0 220	E0.9	64 E	67	20.0	20		22	110	
6025-5-13B	25.4	Ferrous	0.550	50.8	01.5	0.7	20.0	30		23	110	3.2
6025-5-15C	25 /	Stainless	0 220	E0 9	60.7	67	20.0	20		45	120	22
6025-5-13C	23.4	Ferrous	0.550	50.8	80.7	0.7	20.0	30		45	120	5.2
6025-5-15D	25 /	Stainless	0 335	50.8	61.9	67	20.0	29		70	125	22
6025-5-13D	23.4	Ferrous	0.555	50.8	01.5	0.7	20.0	30		70	125	3.2
6025-5-15E	25.4	Stainless	0 470	50.8	81.0	67	20.0	38		90	210	3.2
6025-5-13E	23.4	Ferrous	0.470	50.0	0110	0.7	20.0	50		50		5.2
6025-5-15F	25.4	Stainless	0 470	50.8	79.8	67	20.0	38		140	245	32
6025-5-13F	23.4	Ferrous	0.470	50.0	7510	0.7	20.0	50		140	245	5.2
6025-5-15G	25 4	Stainless	0 480	50.8	81.0	67	20.0	38		180	270	37
6025-5-13G	20.4	Ferrous	0.400	50.0	01.0	0.7	20.0	50		100	270	5.2
6025-5-15H	25.4	Stainless	0 490	50.8	81.0	6.7	20.0	38		230	310	3.2
6025-5-13H		Ferrous	0.450	50.0	0.110	0.7	20.0			250	5.0	
To order, specify	REF N°, i.e.	6025-0-15.						Gener	al Spring Ra	ting Tolerance u	nless sta	ted ±10%

HI-TECH, DOUBLE SEAL, UNITS

nm

LOAD FOR MAXIMUM

DEFLECTION

(mm)

(Kg)

HEVI-LOAD UNITS 0,1,2 & 3

ALWAYSE Hevi-Load Units are designed and manufactured to precise standards.

They offer the highest performance available in load transfer applications with load ball sizes from 12.7mm to 50.8mm diameters and a load capacity range from 35kg to 4000kg used either ball up or ball down.

Hevi-Load Units run on the re-circulating ball principal. The load ball rotates on a bed of small balls supported on a hardened steel, precision machined table.

They can work at maximum capacity in temperatures from - 30°c to +100°c. Drain hole or grease points can be incorporated on request.

No spanner flats for 7110 and 7106 Hevi-Load Units. *Models marked with an asterisk have a bearing shell and are assembled with no felt seal with a chemical black finish for Types 13 and 16.

Type 15 Units (all stainless steel) available on request. When using stainless balls, reduce Type 13 load capacity by 33.3%.

All units are machined using CNC machines from one piece of steel, therefore flanges and threads are integral.

All hevi-load units have an electrophoretic black coated body for corrosion resistance.

HEVI-LOAD 1

Features: High load capacity, bolt fixing. Two spanner flats for fixing and removing. Drill hole fixing. Maximum tightening torques range from 15Nm for M8 to 25Nm for M24.



HEVI-LOAD 0

Features: High load capacity, robust body.

The Hevi-Load 7121 is dimensionally compatible with the Hi-Tech 6025-0.



HEVI-LOAD 2

Features: High load capacity, top flange fixing. The Hevi-Load 7125 is dimensionally compatible with the Hi-Tech 6025-2.



HEVI-LOAD 3

Features: High load capacity, bottom flange fixing. Drill hole fixing. The Hevi-Load 7123 is dimensionally compatible with the Hi-Tech 6025-3.



PATTERN	REF No.	BALL SIZE (mm)	WEIGHT (KGS)			DIN	MENSI	ONS (m	nm)	_		DYNAM CAPA (k	IC LOAD CITY g)
				Α	В		L	N		Р	х	TYPE 13	TYPE 16
				Maximum Diameter	Working Height of Ball		Overall Length	Length of Thread + / - 1mm		Thread Size	Dimension Across Flats	Carbon Steel Balls.	Stainless Steel Balls.
	7101*	12.7	0.036	20.6	19.6							35	35
	7120	25 /	0.394	44.5	41.4							135	135
HEVI-	7121	23.4	0.550	50.8	44.7							320	215
	7150	38.1	1.0	60.0	61.5							1000	670
	7170	50.8	5.02	101.6	98.4							2000	1330
	7180	76.2	14.87	160	145							4000	3000

	7110*	10.7	0.042	20.6	10.6	25.0	16.2	5/16" UNF		25	25	
	7106*	12.7	0.042	20.0	19.0	55.0	10.2	M8		33	35	
	7127		0 / 21	44.5	/19 3	72.4	24.1	1/2" UNF	10	135	125	
	7128	25 /	0.431	44.5	40.5	72.4	24.1	M12	15	155	135	
HEVI- LOAD	7130		0.581	50.8	513	77	25.7	M12	19	320	215	
	7131			50.0	51.5		23.7	1/2" UNF	15	520	215	
	7153	20.1	1 14	60.0	73 5	114 3	40.8	M20	30	1000	670	
	7154	38.1	38.1	1.14	00.0	75.5	114.5	40.0	3/4″UNF	50	1000	070
	7172	50.8	5 26		109.1	150	10.0	M24	29	2000	1220	
	7173		50.8	50.8	5.20	101.0	109.1	139	49.9	1″UNF	30	2000

		0	DIMEN		DYNAM CAPACI	IC LOAD TY (kg)				
Α	В		E	F	G	н	J		TYPE 13	TYPE 1
Maximum Diameter	Working Height of Ball		Distance Under Flange to Base	Flange Thickness	Centres of Fixing Holes	Hole Diameter & Fixing Holes	Major Flange Size		Carbon Steel Balls.	Stainless St Balls.

Hevi-Load ball units Ref. No's 7104 and 7103 have a round flange with two fixing holes.

	7104*	12.7	0.082	23.8	11.2	11.2	3.2	34.8 ±0.2	2x3.6	44.5	
HEVI-	7124	25 /	0.463	44.5	10.3	31.3	4.7	44.5 ±0.2	4x5.6	57.2	
LOAD	7125	23.4	0.746	50.8	13.0	32.0	6.9	57.9	4v7 1	76.2	
2	7152	38.1	1.24	60.0	25.4	35.8	12.4	±0.2	447.1	70.2	Γ
	7171	50.8	6.14	101.6	33.3	65.0	19.0	101.6 ±0.2	4x11	127.0	

General Tolera unless stated :	nce ±0.3mm							To ai	o order, nd TYPE	specify , i.e. 71	REF N° 01-13.	
	7103*	12.7	0.086	23.8	22.6	-	3.2	34.8 ±0.2	2x3.6	44.5		
HEVI-	7122	25 /	0.459	44.5	41.4	-	4.8	44.5 ±0.2	4x5.6	57.2		
3	7123	25.4	0.735	50.8	45.5	-	6.3	57.9	4v7 1	76.2		
	7151	38.1	1.3	60.0	62.2	-	12.4	±0.2	4,7.1	70.2		
	7174	50.8	5.52	101.6	98.3	-	9.6	101.6 ±0.2	4x11	127.0		
	7184	76.2	16.1	160	145	-	15	145± 0.2	4x13	175		



35

135

320

1000

2000

4000

TYPE 16

Stainless Steel Balls.



HEVI-LOAD 5,6 • DIE LIFTERS

HEVI - LOAD 5

Features: High load capacity, greater shock loading protection. Screw fixing collar for Ø38.1mm and Ø50.8mm ball units only, for secure fixing in ball down applications. *Ball units 7107, 7108 and 7109 incorporate the shell ball design and have no seal with a chemical black finish for Types 13 and 16.





HEVI - LOAD 6

Features: Compact, interference fitting, greater shock loading protection. Finish: chemical black housing for Types 13 and 16.



DIE LIFTERS

Features: Tolerance ring for interference fitting for ball up and ball down fitting. Greater shock loading protection. Finish: chemical black housing for Types 13 and 16.



PATTERN	REF No.	BALL	WEIGHT (KGS)			DI	/IENS	SION	IS (r	nm)					D	YNAMIO	LOAD	CAPACITY	(kg)	
		(mm)		A	В	G	Н	L	0	Р	w	Y	z		SUPF LO. (K	PORT AD q)	LOAI MAX DEFLE	D FOR IMUM ICTION	MAXIMUM DEFLECTION (mm)	
				Maximum Diameter	Working Height of Ball	P.C.D. or Centres	Tapped Hole Size	Overall Length	Seating Hole Diameter	Thread Size	Collar Diameter	Minimum Hole Depth	Nut Clearance Diameter		TYPE 13 Carbon Steel Bearings, Zinc Plated Pressings	TYPE 16 Stainless Steel Bearings, Zinc Plated pressings	(K TYPE 13 Carbon Steel Bearings, Zinc Plated Pressings	(g) TYPE 16 Stainless Steel Bearings, Zinc Plated pressings	. ,	
														1		Ge	eneral Spr	ing Rating	Tolerance ±10%	
	7107*		0.067		32.2							30.2			7	7	30	30		
	7108*	12.7	0.007	20.6	31.8		•	47.0	22	M 8	20.6	29.8	16		15	15	35	35	2	
	7109*		0.069		32.2							30.2			25	25	40	40		
	7138				61.9							58.7			7	7	100	100		
	7132		0.517	11 5	61.5			77.0	16			58.3			25	25	110	110		
	7133			44.5	60.7	-		//.0	40			57.5	1		45	45	120	120		
	7134	25 /	0.522		61.9					M10	20 1	58.7			70	70	125	125	3.2	
	7134 7135 7126	0.795	0.795	0.795		81.0		-			WITO	50.1	77.8	22		90	90	210	210	
	7136		0.755	50.8	79.8			08 /	52			76.6			140	140	245	245		
HEVI-	7139		0.804	0.0	21.0			50.4	52			77.9			180	180	270	270		
LOAD	7137		0.813		01.0							11.0			230	230	310	310		
5	7155		1.860		115.5							109.9			225	225	630	630		
	7158		1.940		121.3			161 1				115.7			310	185	685	380		
	7159	20.1	2.040	60.0	128.2	50.	3 3x	101.1	67	M16	E0 0	122.6	22		460	230	765	410	5.6	
	7156	50.1	1.980	00.0	127.0	±0.	2 M5		02	IVITO	59.0	121.4	32		565	375	830	685	5.0	
	7160		2.220		146.1			100 7				139.5	8		690	460	875	660		
	7157		2.620		156.4			105.7				150.8			760	565	910	745		
	7178				179.4							173.1			795	335	1370	660		
	7175	50.8	90_	101 6	177.4	76	4x	200.9	102	M24	101 6	171.1	44		1000	685	1615	955	63	
	7176	50.8	9.0	101.0	174.6	±0.	2 M8	200.8	103	11/24	101.0	168.3			1235	830	1785	1030	0.5	
	7177				171.5							165.2			1560	930	1950	1520		

				•	,	
A	В	D	F	0	S	Y
Maximum Diameter	Working Height of Ball	Body Diameter	Knurl Thickness	Seating Hole Diameter	Base to Top of Body	Minimum Hole Depth

HEVI- LOAD 6 7105 12.7 0.078 25.6 28.5 25.4 8 25.4 +0.05 25.4
--

		D	IME	NSIC	ONS	(mm)	
A	В		D	E	F	ο	S	Y
Maximum Diameter	Working Height of Ball		Body Diameter	Top of Body to Groove	Groove Width	Seating Hole Diameter	Base to top of Body	Minimum Hole Depth

	DL-24	12.7	0.074	24.5	30		23.9	9	10.5	24.1	28.5	28.6
DIE	DL-30	15.8	0.127	30.5	36		29.9	12	10.5	30.1	34.5	34.6
LIFTERS	DL-40	25.4	0.320	40.5	48		39.8	12	10.5	40.1	46.5	46.6
	DL-50	30	0.660	50.5	60		49.9	15	12.3	50.1	58.5	58.6
	DL-70	38.1	2.000	71	80		70	19	19	70.2	78	78.1
To order, specify REF N° and TYPE, i.e. 7107-13.												

Maximum

General Spring Rating Tolerance ±10%

40	40	90	90	1.5
60	60	110	110	1.5
100	100	175	175	1.5
335	200	585	465	1.5
500	325	720	570	2

25

25

40

40

2

General Tolerance unless stated ±0.3mm

ALWAYSE

SPRING LOADED UNITS

ALWAYSE spring loaded units are used in applications such as:-

Guillotines; Presses; Moulding Machines; Tool Bases; Press Brakes; Shock Loading applications.

Spring loaded ball units reduce damage caused by shock loads. They also allow for dimension changes due to temperature and self-adjust to evenly distribute loads.

1507, 1508 and 1509 Units

These units incorporate a plastic scraper seal, which keeps debris outside the ball unit.

Spring loaded ball unit sizes Ø31.7mm, Ø39.7mm and Ø50.8mm have dirt exit holes as standard. All other spring loaded ball units have felt or foam seals as standard.

Spring loaded ball units can be used as die-lifters, inverted or at an angle.

See pages 24 and 25 for details of our Hevi-Load spring loaded ball units and Die-Lifter ball units.

Completely stainless steel (Type15) spring loaded ball units also available upon request with reduced support loads and depress loads.

Spring loaded ball units with ball sizes of Ø25.4mm also available upon request with nylon load ball and stainless bearings (Type 14).

The Type 14 ball units are suitable for light load applications and when object surface protection is required.

The 1507 and 1509 ball units have 2mm thick pressed steel flanges.

Do not remove the circlip on any of the spring loaded ball units.

* Other loads available upon request.

5320 / 5330 / 5345

The 5320 / 5330 / 5345 ball units are assembled with standard 522-0 or 530-0 or 545-0 Euro ball unit (see pages 16-17). The ball units have a dirt exit hole.



LARGE TOP FLANGE

Features: Large top flange fixing. Low profile. The 1507 has a pressed steel flange 2mm thick similar to Small Top Flange image below.





PLAIN BODY



LARGE BOTTOM FLANGE

Features: Large bottom flange fixing. High profile.



(1032 shown here)



SMALL TOP FLANGE

Features: Small flange. Low profile.

REF No.	BALL SIZE	WEIGHT (KGS)			DIN	IENSIONS (SUPPORT DYNAMIC LOAD (kg)	LOAD TO FULLY DEPRESS (kg)				
	(mm)		A	ght	D te	F	tres D	er of & H Holes	L		TYPE 13 Carbon Steel Bearings, Zinc		
			Maximum Diameter	Working Hei of Ball	Body Diame	Flange Thick	P.C.D. or Cen of Fixing Ho	Hole Diamet Fixing Holes No. of Fixing	Overall Heig		Plated Pressings TYPE 16 Stainless Steel Bearings, Zinc Plated Pressings		
LARGE T	OP FLA	NGE											
3011	19	0.42	66.6 +0.0 -1.0	11.4	36.5	7.9	50.8 ±0.2	3x 7	63		10	30	
1018	25.4	0.57	75 +0.0 -1.0	13.8	44.5	7.9	60.3 ±0.2	3x 7	67.1		35	100	
1507	25.4	0.40	71.3	19.3	44.5	2	60.4 ±0.2	2x 5.1	72.2		50	130	
1028	31.7	1.16	89 +0.0 -1.0	17	60.0	9.5	73 ±0.2	3x 7	94.5		100	180	
2010	39.7	2.04	101.6 +0.0 -1.0	17.7	69.8	515	85.7 ±0.2	Зх	107.7			170	
4008	50.8	5.1	152.4 +0.0 -1.0	25.7	101.6	12.7	127 ±0.2	9	139.7		170	410	
LARGE B	οττοιν	I FLANG	E										
3012	19	0.42	66.6 +0.0 -1.0	65.1	36.5	7.9	50.8 ±0.2	3x 7	-		10	35	
1510	25.4	0.45	75 +0.0 -1.0	72.9	44.5	7.9	60.3 ±0.2	3x 7	-		50	130	
1032	31.7	1.02	89 +0.0 -1.0	95.3	60.0	9.5	73 ±0.2	3x 7	-		100	200	
5320 / 53	330 / 5 3	845											
5320	22.2	0.26	50	18.5 ±0.2	39	14	-	-	51.5		72	160*	
5330	30	0.52	62	24.4	48.2	17.7	-	-	70		141	201	
5345	44.45	1.40	85	35.6	66.4	24.2	-	-	100.5		232	420	
PLAIN BO	DDY										* Other loads av request.	vailable upon	
3009	19	0.26	-	9.5	36.5				65.1		10	35	
1016	25.4	0.38	-	11.9	44.5				70.6		35	140	
1508	25.4	0.38		12.5	44.5				72.9		50	130	
1026	31.7	0.86	-	10.4	60.0				94.5		100	200	
2008	39.7	1.46	-	12.7	69.8				107.6			190	
4006	50.8	4.2	-	13	101.6				139.7		170	410	
SMALL T	OP FLA	NGE											
3010	19	0.30	45 +0.0 -1.0	11.4	36.5	7.9			63		10	30	
1017	25.4	0.44	50 +0.0 -1.0	13.8	44.5	7.5			67.1		35	100	
1509	25.4	0.39	56	19.3	44.5	2		-	72.2		50	130	
1027	31.7	0.99	75 +0.0	17	60.0	9.5			94.6		100	180	
2009	39.7	1.8	-1.0	17.7	69.8				107.7			170	
4007	50.8	4.4	114.3 +0.0 -1.0	25.7	101.6	12.7			139.7		170	410	

General Spring Rating Tolerance ±10% General Tolerance unless stated ±0.3mm ALWAY

SPRING LOADED UNITS

TUFF SERIES HEAVY DUTY UNITS

ALWAYSE *TUFF* SERIES Heavy Duty units are built to provide a long working life and to withstand harsh conditions.

They have a solid machined body with chrome steel bearings and incorporate both dust seal and dirt exit hole (except No. 0519).

They provide a higher load capacity than standard units.

Solid steel body for attachment purposes, but not shock loading. Body chemical black finish for types 13 and 16.

All units are machined using CNC machines from one piece of steel, therefore flanges and threads are integral.

ALSO AVAILABLE

All patterns (i.e.: 21,22,23 and 24) of ref nos 0519, 3019 and 1019 are available with a nylon main ball (Type 14) ideal for light load and reduced marking

TUFF HEAVY DUTY 21

Features: Plain solid machined body.



TUFF HEAVY DUTY 22

Features: Flange fixing either by using rivets or screws.



TUFF HEAVY DUTY 23

Features: Bolt, drilled hole fixing. Maximum tightening torques range from 10Nm for M6 to 20Nm for M12.



TUFF HEAVY DUTY 24

Features: Bottom flange fixing either by using rivets or screws. Drilled hole fixing.





5

REF No.	BALL SIZE	WEIGHT (KGS)			 	DIN	IENSIC	ONS (n	nm)					DYN/ LO/ CAPACI	AMIC AD TY (ka)
	(mm)		Maximum Diameter B	Working Height B of Ball	Body Diameter D	Distance Under m Flange to Base	Flange Thickness	Centres of Fixing Holes	Hole Diameter of Fixing Holes	Major Flange Size	Length of Thread A +/1mm	Thread Size	Base to Top of v Body	TYPE 13 Carbon Steel Bearings, Zinc Plated Pressings TYPE 16 Stainless Steel Bearings, Zinc Plated Pressings	TYPE 15 Stainless Stee Bearings and Pressings

0519-21		0.036	20	20	-	-	-	-	-	-	-	-	17		
0519-22	12.7	0.051	32	12	20	8	4	26 ±0.2	3.5	-	-	-	17	25	25
0519-23		0.042	20	20	-	-	-	-	-	-	28	M6	17		
0519-24		0.096	20	25	-	-	6	24 ±0.2	6.5	35	-	-	22		

3019-21		0.120	30	30	-	-	-	-	-	-	-	-	26		
3019-22	19	0.168	50	14	30	16	5	40 ±0.2	5	-	-	-	26	50	50
3019-23		0.124	30	30	-	-	-	-	-	-	25	M8	26		
3019-24		0.220	30	35	-	-	6	31 ±0.2	6.5	44.5	-	-	31		

1019-21		0.177	35	35	-	-	-	-	-	-	-	-	28		
1019-22	25.4	0.282	60	20	40	15	5	49 ±0.2	5	-	-	-	28	125	125
1019-23		0.190	35	35	-	-	-	-	-	-	40	M8	28		
1019-24		0.294	35	40	-	-	6	35 ±0.2	7	50	-	-	33		

1029-21		0.486	50	45	-	-	-	-	-	-	-	-	37		
1029-22	31.7	0.584	75	24	50	21	5	62.5 ±0.2	5	-	-	-	37	250	250
1029-23		0.500	50	45	-	-	-	-	-	-	40	M10	37		
1029-24		0.740	50	50	-	-	8	49 ±0.2	7	63.45	-	-	42		

2019-21		0.850	60	55		-	-	-	-	-	-	-	-	46		
2019-22	39.7	0.960	84	27		60	28	5	72 ±0.2	6	-	-	-	46	500	250
2019-23		0.900	60	55		-	-	-	-	-	-	50	M12	46		
2019-24		1.350	60	60		-	-	10	60 ±0.2	7	80	-	-	51		

General Tolerance unless stated ±0.3mm

To order, specify REF N° and TYPE, i.e. 0519-21-13.

MALWAYSE

FIXING CLIPS

ALWAYSE provide a complete range of fixing clips designed specially for use with their ball transfer units.

They lock the unit securely in position without the need for special tools or machinery.

Some standard clips are described here. Special designs can also be provided, please ask for details.

The effectiveness and security of ball units attached by means of fixing clips can be influenced by size of fixing holes, table thickness and ball unit tolerances.

CL11 (stock item)

Available in three sizes only to suit ball units with body diameters of 36mm, 45mm and 62mm.

CL12 (made to order)

This clip will fit under the flange of any of our ball units that have parallel sides. If any particular size of clip is not in stock there may be a minimum order charge. Fixing hole sizes on application.

On certain units it is possible to machine a recess to retain the clip in the body of the ball unit. These units must have a solid steel body, are not stock items and are only manufactured to specific orders.

CL13 (stock item)

These are to be used with ball units with a body diameter of 24mm only.

CL14 (stock item)

Stocked for body diameter of 24mm, 36mm, 45mm and 62mm. This clip was designed for fixing ball units from the top face of a ball platform. The clip can also be used for fixing the ball unit from underneath the ball platform if clip CL11 is not suitable. The preferred table top material thickness for maximum effectiveness of the CL14 range of clips is 2mm to 4mm. The CL14 fixing clips can be used for thicker materials with a slight reduction in clip effectiveness. For maximum clip effectiveness the seating hole size should be on the minimum tolerance and the table top material thickness should be 4mm. Please see page 17 for seating hole sizes

CL14 fixing clips must be placed into the seating hole first, before the ball unit is fitted.







CL13







CL15 (made to order)

A circlip type clip used mainly for solid machined body units. The circlip is fitted from underneath the ball unit and is available in many sizes.

Ball units with circlip grooves are not ex stock items. The standard circlip is self colour spring steel, but plated circlips can be offered where corrosion resistance is required.

FITTING CL12 AND CL14 FIXING CLIPS

When fitting ball units with CL12 or CL14 fixing clips, do not strike the load ball to press the unit into position.

Instead, apply an even force onto the ball unit's body using a tube or similar tool.

Installation and removal tools can be supplied to ensure the correct installation of ball transfer units for the CL12 and CL14 fixing clip range. Details of the installation and removal tools are available upon request.



CL1



IXING CLI	PS
IXING CI	
DNIXI	U
NIXI	U
X	Ż

REF No								
		Ref No.	Flange di A	ameter	Inside diar B	meter	Material Thickness D	
CI 11		CL11-22 CL11-30 CL11-45	Ø71 Ø72	.1 .1 2.6	Ø35.9 Ø44.9 Ø61.2	9	0.7 0.7 0.7	
CLII	Material: Carbon Spring Steel and Stainless Steel AISI 304	CL11 CL11- 522-0, 522-4 (pages 16	CLIP TO BE 22 and 522-6 5 & 17)	USED WI 530-0, 5 (pag	TH THE FOL CL11-30 530-4 and 530 ges 16 & 17)	-LOWING	BALL UNITS CL11-45 45-0, 545-4 and 545-6 (pages 16 & 17)	
	(CL11-45 SS Only) Finish: Zinc Plated and Self Colour For Stainless Steel	(pages 18	3 & 19)	806-30, 8 (pag	-30, 805-30 07-30 and 81(ges 18 & 19)	0-30	800-45, 80545 and 810-45 (pages 18 & 19)	
		CL12 1007	CLIP TO BE	USED W , 515-4, 51 , 522-4, 52	ITH THE FO	LLOWING	BALL UNITS 5-4 7104, 7124 7125, 7152 and 7171	-
CI 12		(Pages 8 & 9) (Pag	, 530-4, 530 , 545-4, 54 ges 16 & 17	5-6) (Pag	ges 20 & 21	(Pages 22 & 23)	_
		0519-22, 3019 1019-22, 1029 and 2019-22	-22 810 -22 810 2 805 800 800 810-4	-15, 800-22 -22, 800-30 -30, 810-30 -45, 805-45 -30, 807-30 5 and 800-	2 3010 0 1018 0 1027 5 2010 60), 3011, 10 ⁷ 8, 1509,150 7, 1028, 200 0, 4007 and 4008	17 17 19 d	
	Material: Stainless Steel Spring Steel	(Pages 28 & 2	(Pag	ges 18 & 19) (Pag	ges 26 & 27	')	
						upon rec	Juest	
			Flange	diamotor	Incido	diamotor	longth	1
		Ref No.	liange	A		B	C	
CL13		CL13-15	Ø	41.4	Ø	23.4	3.2	
		The CL13- ball units (p	15 fixing cli ages 16-17)	p can be and also	used with t the 810-15	he 515-0. ball unit	515-4 and 515-6 (pages 18 and 19).	
	Material: Carbon Spring Steel Finish: Bronze Finish							
		Ref No.	Flange diameter A	Body dia	outside Imeter B	Length C	Material Thickness D	
		CL14-15 CL14-22	Ø30.9 Ø44.5	2	024.7 036.7	6.0 7.0	0.3	
CL14		CL14-30 CL14-45	Ø74.0		062.7	7.0 7.0		-
		CL14-15 515-0, 515-4 ar 515-6	nd 522-	<u>L14-22</u> 0, 522-4 and 522-6	530-	<u>CL14-30</u> 0, 530-4 and 530-6	CL14-45 545-0, 545-4 and 545-6	-
		(pages 16 & 17 7104 (pages 22 & 23 810-15	7) (pag 800 3) (pag	g <u>es 16 & 17)</u> I-22, 810-22 ges 18 & 19)	(pac 800-30, 807-3 (pac	ges 16 & 17) 805-30, 806- 0 and 810-30 res 18 & 19)	(pages 16 & 17) 30 800-45, 805-45) and 810-45 (pages 18 & 19)	
	Material: Carbon Spring Steel Finish: Zinc Plated	(pages 18 & 19))		1017 a (pag	7, 1018, 1507 and 1509 ges 26 & 27) 7124		
	Please see page 17 for seating hole sizes				(pag	ges 22 & 23)]
								7
		10 CL15	04 04	USED WI 7104 715	TH THE FOL , 7124, 7125 2 and 7171	0519	-22, 3019-22, 1019-22	
CI 15		(pages	8 & 9)	(pag	jes 22 & 23)	10	(pages 28 & 29)	
		800-30, 805	-22, 810-22 -30, 810-30 -45, 810-45	1509, 15	507, 1017, 101 507, 1027, 102 , 2010, 4007	28		
		and 8 (pages 18	00-60 3 and 19)	a (page	nd 4008 es 26 and 27)			
	Material: Carbon Spring Steel and Stainless Steel Spring Steel Finish: Self Colour	Bal	l units with CL15 fixir	circlip gr ng clip siz	ooves are a es available	vailable o upon re	on request quest	

To order, specify REF N° i.e. CL11-22. For CL12 and CL15 clips specify REF N° and ball unit REF N° i.e. CL12,1007.

TEE BLOCKS, DIE TABLES

TEE BLOCKS

Single Minute Tool and Die Changing

Our comprehensive range of tee blocks and spring loaded ball transfer units, set into the bed of your power press or machine tool, will allow effortless positioning of tooling but still allow rigid clamping.

We supply tee blocks for both standard and non-standard tee slots the length, pitch, ball height etc. being dependant on tool weight and profile.

Other sizes available on request.

Standard Finish is chemical black.



QUICK CHANGE DIE TABLES

For all types of moulding and stamping applications.

They allow quick, easy tool changing with storage close to the machine. All tables are fully guarded. Access to the machine via a lift-up gate if required.

Custom designed to your specific requirements, installation is carried out by our engineers.

NOTE - safety rails should be fitted where there is the possibility of loads rolling off.



TEE BLOCKS

Tee blocks can be designed and manufactured to suit particular applications. See pages 24 & 25 for our range of Die Lifter ball units.





ALWAYSE ENGINEERING LIMITED - TERMS AND CONDITIONS OF SALE

1 Interpretation

1.1 In these Terms Conditions:

"COMPANY" means Alwayse Engineerin Limited

"CONTRACT" means the contract for the purchase and sale of the Goods

"CUSTOMER" means the person or company who accepts a quotation of the Company for the sale of the Goods, or whose order for the Goods is accepted by the Company

"GOODS" means the goods which the Company is to supply in accordance with these Terms and Conditions

1.2 Any reference in these Terms and Conditions to any provision of a statute shall be construed as a reference to that provision as amended, reenacted or extended at the relevant time.

2 Basis of the Sale

2.1 The Company shall sell and the Buyer shall purchase the Goods in accordance with any written quotation of the Company which is accepted by the Buyer within 60 days of its date, or any written order of the Buyer which is accepted by the Company, subject in either case to these Terms and Conditions, which shall govern this Contract to the exclusion of any other terms and conditions subject to which any such quotation is accepted or purported to be accepted, or any such order is made or purported to be made, by the Buyer.

2.2 No order submitted by the Buyer shall be deemed to be accepted by the Company unless and until confirmed in writing by the Company's authorised representative.

3 Price of the Goods

3.1 The price of the Goods shall be the Company's quoted price or, where no price has been quoted (or a quoted price is no longer valid), the price listed in the Company's published price list current at the date of delivery of the Goods

3.2 The Company reserves the right, by giving notice to the Buyer at any time before delivery, to increase the price of the Goods to reflect any increase in the cost to the Company which is due to any factor beyond the control of the Company.

3.3 The price is exclusive of delivery, handling, administration and packaging charges and any applicable value added tax, which the Buyer shall be additionally liable to pay to the Company.

4 Delivery

4.1 Unless otherwise provided in the Contract, delivery of the Goods shall be made by the Company at the Buyer's premises

4.2 The Contract price does not include the cost of off-loading and assembly, which shall be arranged by the Buyer and performed at its own expense and risk unless otherwise agreed in writing.

4.3 Any dates quoted for delivery of the Goods are approximate only and the Company shall not be liable for any delay in delivery of the Goods but shall use its reasonable endeavours to deliver on the quoted date. Time for delivery shall not be of the essence of the Contract

4.4 If the Buyer does not accept delivery when tendered by the Company the Buyer shall be liable for any storage, administration, carriage and re-delivery charges.

5 Risk and Property

5.1 Risk of damage to or loss of the Goods shall pass to the Buyer:

5.1.1 in the case of Goods to be delivered at the Company's premises, at the time when the Company notifies the Buyer that the Goods are available for collection; or

5.1.2 in the case of Goods to be delivered otherwise than at the Company's premises, at the time of delivery or, if the Buyer wrongfully fails to take delivery of the Goods, the time when the Company has tendered delivery of the Goods 5.2 Notwithstanding delivery and the passing of risk in the Goods, or any other provision of these Terms and Conditions, the property in the Goods shall not pass to the Buyer until the Company has received in cash or cleared funds payment in full of the price of the Goods and all other goods agreed to be sold by the Company to the Buyer for which payment is then due.

5.3 Until such time as the property in the Goods passes to the Buyer, the Buyer shall hold the Goods as the Company's fiduciary agent and bailee, and shall keep the Goods separate from those of the Buyer and third parties and properly stored, protected and insured and identified as the Company's property, but shall be entitled to resell or use the Goods in the ordinary course of its business providing that the proceeds of such sale shall be held upon trust for the Company. Where the Buyer does sell or pledge the Goods it shall hold the proceeds of sale or charging as fiduciary agent of the Company and forward the same to the Company.

5.4 Until such time as the property in the Goods passes to the Buyer (and provided the Goods are still in existence and have not been resold), the Company shall be entitled at any time to require the Buyer to deliver up the Goods to the Company and, if the Buyer fails to do so forthwith, to enter upon any premises of the Buyer or any third party where the Goods are stored and repossess the Goods.

5.5 The Buyer shall not be entitled to pledge or in any way charge by way of security for any indebtedness any of the Goods which remain the property of the Company, but if the Buyer does so all moneys owing by the Buyer to the Company shall (without prejudice to any other right or remedy of the Company) forthwith become due and payable.

6 Limitation of Liability

6.1 All warranties, conditions or other terms employed by statute or common law are excluded to the fullest extent permitted by law.

6.2 Any claim by the Buyer which is based on any defect in the quality or condition of the Goods or their failure to correspond with specification shall (whether or not delivery is refused by the Buyer) be notified to the Company within 7 days from the date of delivery or (where the defect or failure was not apparent on reasonable inspection) within 2 months after delivery of the Goods. If delivery is not refused, and the Buyer does not notify the Company accordingly, the Buyer shall not be entitled to reject the Goods and the Company shall have no liability for such defect or failure, and the Buyer shall be bound to pay the price as if the Goods had been delivered in accordance with the Contract.

6.3 Where any valid claim in respect of any of the Goods which is based on any defect in the quality or condition of the Goods or their failure to meet Company specification is notified to the Company in accordance with these Terms and Conditions, the Company shall be entitled to replace the Goods (or the part in question) free of charge or, at the Company's sole discretion, refund to the Buyer the price of the Goods (or a proportionate part of the price), but the Company shall have no further liability to the Buyer.

6.4 Except in respect of death or personal injury caused by the Company's negligence, the Company shall not be liable to the Buyer by reason of any representation (unless fraudulent), or any implied warranty, condition or other term, or any duty at common law, or under the express terms of the Contract, for any indirect, special or consequential loss or damage (whether for loss of profit or otherwise), costs, expenses or other claims for compensation whatsoever (whether caused by the negligence of the Company, its employees or agents or otherwise) which arise out of or in connection with the supply of the Goods or their use or resale by the Buyer, and the entire liability of the Company under or in connection with the Contract shall not exceed the price of the Goods, except as expressly provided in these Terms and Conditions.

6.5 The Company shall have no liability whatsoever where the Goods have not been maintained or used in accordance with their recommended specifications and maintenance schedules as updated from time to time by the Company.

6.6 The Seller shall not be liable for any delay or failure attributable to any cause beyond the Seller's reasonable control including without limitation fire, strike, act of god and embargo.

Terms of Payment

7

7.1 The Buyer shall pay the price of the Goods in pounds sterling (without any deduction) within 30 days of the date of the Company's invoice, and the time of payment of the price shall be of the essence of the Contract.

7.2 If the Buyer fails to make any payment on the due date then, without prejudice to any other right or remedy available to the Company, the Company shall be entitled to:

7.2.1 cancel the Contract or suspend any further deliveries to the Buyer;

7.2.2 appropriate any payment made by the Buyer to such of the Goods (or the goods supplied under any other contract between the Buyer and the Company) as the Company may think fit; and

7.2.3 charge the Buyer interest (both before and after any judgement) on the amount unpaid, at the rate of 3 per cent per annum above Barclays Bank Plc base rate from time to time, until payment in full is made (a part of a month being treated as a full month for the purpose of calculating interest).

7.2.4 set of any monies due to the Buyer on any account whatsoever against monies due to the Buyer from the Company

7.3 Where the Company agrees to invoice in a currency other than sterling the Buyer shall be liable for all currency conversion brokerage or other charges and ensure that the sum payable to the Company when converted to pounds Sterling is not less than the amount payable in pounds sterling on the date of quotation

8 Insolvency of Buyer

8.1 This clause applies if:

8.1.1 the Buyer makes any voluntary arrangement with its creditors or (being an individual or firm) becomes bankrupt or (being a company) becomes subject to an administration order or goes into liquidation (otherwise than for the purposes of amalgamation or reconstruction); or

8.1.2 an encumbrancer takes possession, or a receiver is appointed, of any of the property or assets of the Buyer; or

8.1.3 the Buyer ceases, or threatens to cease, to carry on business; or

8.1.4 there is a change in control of the ownership of the Company or its shares

8.1.5 the Company reasonably apprehends that any of the events mentioned above is about to occur in relation to the Buyer and notifies the Buyer accordingly.

8.2 If this clause applies then, without prejudice to any other right or remedy available to the Company, the Company shall be entitled to cancel the Contract or suspend any further deliveries under the Contract without any liability to the Buyer, and if the Goods have been delivered but not paid for, the price shall become immediately due and payable notwithstanding any previous agreement or arrangement to the contrary.

General

9

9.1 No waiver by the Company of any breach of the contract by the Buyer shall be considered as a waiver of any subsequent breach of the same or any other provision.

9.2 This Contract shall be governed by the laws of England, and the Buyer agrees to submit to the non-exclusive jurisdiction of the English courts.

© This brochure is the copyright of Alwayse Engineering Limited and is fully protected. Nothing may be reprinted or reproduced in whole or part without the written consent of Alwayse Engineering Limited





ALWAYSE ENGINEERING LIMITED MILLER STREET BIRMINGHAM B6 4NF ENGLAND + 44 (0) 121 380 4700 Telephone: 0121 380 4700 Fax: 0121 380 4701 + 44 (0) 121 380 4701 web: www.alwayse.co.uk email: sales@alwayse.co.uk