




PNEUMATIC COUPLINGS  
PNEUMATISCHE KUPPLUNGEN

SERIE 026B

DN 7.2



**Materials**




**Material Code**

A = Brass


B = Brass

C = Brass

S = Brass




0 - 35 bar  
(0-508 PSI)



-20° to + 100°C (NBR)  
-4° to + 212°F



**Shut Off Type**




OM 262 - 00990  
OM 200 - 00650

**FLOW** 700 lt/min

**DN 7.2 mm**




**Options**

FPM

NICKEL

**Plug Profile Serie 026B**




**Compatible with**


TST 025B  
PARKER - RECTUS 25KB, 26KB




## QUICK COUPLINGS SCHNELLKUPPLUNGEN




Connection	Part No.	SW	L	ØD
BSP 1/8"	026 EGB 10	21	40,3	24,7
BSP 1/4"	026 EGB 13	21	41,3	24,7
BSP 3/8"	026 EGB 17	21	41,3	24,7
BSP 1/2"	026 EGB 21	21	44,3	24,7
M 14 x 1,5	026 EGBM 14	21	42,3	24,7
M 16 x 1,5	026 EGBM 16	21	42,3	24,7
M 18 x 1,5	026 EGBM 18	21	42,3	24,7




Connection	Part No.	SW	L	ØD
BSP 1/8"	026 DGB 10	21	39,3	24,7
BSP 1/4"	026 DGB 13	21	41,3	24,7
BSP 3/8"	026 DGB 17	21	41,3	24,7
BSP 1/2"	026 DGB 21	24	43,8	24,7
M 14 x 1,5	026 DGBM 14	21	40,3	24,7
M 16 x 1,5	026 DGBM 16	21	40,3	24,7
M 18 x 1,5	026 DGBM 18	21	40,3	24,7




Connection	Part No.	SW	L	ØD
6 mm - 1/4"	026 HGB 06	21	55,3	24,7
8 mm - 5/16"	026 HGB 08	21	55,3	24,7
9 mm - 5/14"	026 HGB 09	21	55,3	24,7
10 mm - 3/8"	026 HGB 10	21	55,3	24,7
13 mm - 1/2"	026 HGB 13	21	55,3	24,7



Connection	Part No.	SW	L	ØD
6 x 8 mm - M 12 x 1	026 PGB 06	21	46,3	24,7
8 x 10 mm - M 16 x 1	026 PGB 08	21	49,3	24,7
9 x 12 mm - M 16 x 1	026 PGB 09	21	49,3	24,7



Connection	Part No.	SW	L	ØD
6 mm - M 12 x 1	026 MGB 06	21	63,3	24,7
8 mm - M 12 x 1	026 MGB 08	21	63,3	24,7
10 mm - BSP 1/4"	026 MGB 10	21	63,3	24,7



Connection	Part No.	SW	L	ØD
6 x 8 mm - M 12 x 1	026 YGB 06	21	126,8	24,7
8 x 10 mm - M 16 x 1	026 YGB 08	21	143,8	24,7
9 x 12 mm - M 16 x 1	026 YGB 09	21	143,8	24,7